

CELSIUS HAMMAM



Hammam



Hammam Hydro

DIMENSIONS

120x120 H223
150x120 H223
150x150 H223

200x120 H223
200x150 H223

FUNCTIONS

	HAMMAM	HAMMAM HYDRO
Electronic panel with 3 heat settings	●	●
Bench	1	1
Glass thickness 8 mm	●	●
Lacquered steel handle	●	●
Aroma vapouriser	●	●
Vertical whirlpool (12 jets)	-	●
Thermostatic mixer and hand shower	●	●
Shower head 30x30 cm with waterfall	-	●
External side mirror	●	●
LED lighting	●	●
Bluetooth sound system	OPTIONAL	OPTIONAL
LED Chromolight	OPTIONAL	OPTIONAL
Hanger	OPTIONAL	OPTIONAL
Emergency button ¹	OPTIONAL	OPTIONAL
Semi-automatic boiler descaling system ²	OPTIONAL	OPTIONAL

FRAME COLOUR

External frame profile, handle, door hinge



8Y Tent grey




8W Dusty grey



86 Gravel grey

HAMMAM

Internal walls, tray, roof, seat




Matt white


INSTALLATION




In recess



Right corner



Left corner



Centre of wall

¹ Functions as product switch-off, alarm sound, light switch-on, remote alarm contact shut-off.

² INTENSIVE USE: it is mandatory to install a reverse osmosis demineraliser (2°F) to remove any minerals in the water from the steam generator; INTERMITTENT USE: we recommend a semi-automatic boiler descaling system, requiring a maintenance and cleaning procedure every 500 hours approximately. The costs of ordinary boiler descaling maintenance are charged on the customer.



CELSIUS HAMMAM 120x120

Installation	Code	Side panel		Functions			Boiler Descaling		Frame Colour		
		Glass	Wall	White LED	Chromolight+ Audio BT	Chromolight+ Audio BT+ Emergency	Without	With	Tent Grey	Dusty Grey	Gravel Grey

HAMMAM 120X120 H223

		G	W	0	6	7	X-	C-	8Y	8W	86
In recess	CL021212BI										
Right corner	CL021212AD										
Left corner	CL021212AS										
Centre of wall	CL021212CP										

HAMMAM HYDRO 120X120 H223

		G	W	0	6	7	X-	C-	8Y	8W	86
In recess	CLH21212BI										
Right corner	CLH21212AD										
Left corner	CLH21212AS										
Centre of wall	CLH21212CP										

CELSIUS HAMMAM 150x120

Installation	Code	Side panel		Functions			Boiler Descaling		Frame Colour		
		Glass	Wall	White LED	Chromolight+ Audio BT	Chromolight+ Audio BT+ Emergency	Without	With	Tent Grey	Dusty Grey	Gravel Grey

HAMMAM 150X120 H223

		G	W	0	6	7	X-	C-	8Y	8W	86
In recess	CL021512BI										
Right corner	CL021512AD										
Left corner	CL021512AS										
Centre of wall	CL021512CP										

HAMMAM HYDRO 150X120 H223

		G	W	0	6	7	X-	C-	8Y	8W	86
In recess	CLH21512BI										
Right corner	CLH21512AD										
Left corner	CLH21512AS										
Centre of wall	CLH21512CP										

Code composition = Code + Side panel + Functions + Boiler Descaling + Frame colour



CELSIUS HAMMAM 200x120

Installation	Code	Side panel		Functions			Boiler Descaling		Frame Colour		
		Glass	Wall	White LED	Chromolight+ Audio BT	Chromolight+ Audio BT+ Emergency	Without	With	Tent Grey	Dusty Grey	Gravel Grey

HAMMAM 200X120 H223

		G	W	0	6	7	X-	C-	8Y	8W	86
In recess	CL022012BI										
Right corner	CL022012AD										
Left corner	CL022012AS										
Centre of wall	CL022012CP										

HAMMAM HYDRO 200X120 H223

		G	W	0	6	7	X-	C-	8Y	8W	86
In recess	CLH22012BI										
Right corner	CLH22012AD										
Left corner	CLH22012AS										
Centre of wall	CLH22012CP										

CELSIUS HAMMAM 150x150

Installation	Code	Side panel		Functions			Boiler Descaling		Frame Colour		
		Glass	Wall	White LED	Chromolight+ Audio BT	Chromolight+ Audio BT+ Emergency	Without	With	Tent Grey	Dusty Grey	Gravel Grey

HAMMAM 150X150 H223

		G	W	0	6	7	X-	C-	8Y	8W	86
In recess	CL021515BI										
Right corner	CL021515AD										
Left corner	CL021515AS										
Centre of wall	CL021515CP										
Centre of wall right	CL021515CD										
Centre of wall left	CL021515CS										

HAMMAM HYDRO 150X150 H223

		G	W	0	6	7	X-	C-	8Y	8W	86
In recess	CLH21515BI										
Right corner	CLH21515AD										
Left corner	CLH21515AS										
Centre of wall	CLH21515CP										
Centre of wall right	CLH21515CD										
Centre of wall left	CLH21515CS										

Code composition = Code + Side panel + Functions + Boiler Descaling + Frame colour



CELSIUS HAMMAM 200x150

Installation	Code	Side panel		Functions			Boiler Descaling		Frame Colour		
		Glass	Wall	White LED	Chromolight+ Audio BT	Chromolight+ Audio BT+ Emergency	Without	With	Tent Grey	Dusty Grey	Gravel Grey

HAMMAM 200X150 H223

		G	W	0	6	7	X-	C-	8Y	8W	86
In recess	CL022015BI										
Right corner	CL022015AD										
Left corner	CL022015AS										
Centre of wall	CL022015CP										
Centre of wall right	CL022015CD										
Centre of wall left	CL022015CS										


HAMMAM HYDRO 200X150 H223



		G	W	0	6	7	X-	C-	8Y	8W	86
In recess	CLH22015BI										
Right corner	CLH22015AD										
Left corner	CLH22015AS										
Centre of wall	CLH22015CP										
Centre of wall right	CLH22015CD										
Centre of wall left	CLH22015CS										

Code composition = Code + Side panel + Functions + Boiler Descaling + Frame colour




CELSIUS HAMMAM 120x120 WALL


 Power supply: 3kW




NICHE W




RIGHT CORNER W




LEFT CORNER W





CENTRE OF WALL W




CELSIUS HAMMAM 150x120 WALL


 Power supply: 4,5kW




NICHE W




RIGHT CORNER W




LEFT CORNER W




CENTRE OF WALL W




CELSIUS HAMMAM 200x120 WALL


 Power supply: 4,5kW




NICHE W




RIGHT CORNER W




LEFT CORNER W





CENTRE OF WALL W




CELSIUS HAMMAM 150x150 WALL


 Power supply: 4,5kW




NICHE W




RIGHT CORNER W




LEFT CORNER W





CENTRE OF WALL W




CELSIUS HAMMAM 150x150 GLASS




 Power supply: 4,5kW




CELSIUS HAMMAM 200x150 WALL





 Power supply: 6kW



CELSIUS HAMMAM 200x150 GLASS



 Power supply: 6kW



Electrical features:

Voltage: 230V 1P+N / 400V 3P+N - 50/60Hz

Set-ups:

Hammam
Hammam Hydro

Hydraulic features:

Working pressure 2-5bar
Hot/Cold water 1/2" shower
Cold water 1/2" Steam generator*
Syphon connection Ø40 mm



*Steam generator water supply:

For intensive use, it is mandatory to install a reverse osmosis water demineraliser (2°F). For occasional use, a semi-automatic boiler descaling system is available